TATRAFAN ENVIRO®
FROM WASTE TO VALUE

REGRANULATE ABS-OST1-GRAY

This material sheet serves as a general product characteristic for customer needs.
It contains individual specification, composition and use of this material.

REGRANULATE ABS-OST1-GRAY is made by regranulation of molding items and inlets from injection moulding process. The regranulate has lentil shape, 4 - 6 mm in size, and gray colour. It is suitable for further processing into technical plastic and consumer plastic products using injection moulding, pressing and extrusion technology. The material is not suitable for products with the direct contact with food. Every customer is required to review this material for the intended use.

TECHNICAL DATA

REGRANULATE ABS-OST1-GRAY	**Composition**	100% ABS, GRAY
	Melt index	5,0 - 6,0g/10min. /210°C, 2,16 kg/
	Density	1,03 - 1,05g/cm^3 ISO 1183
	Particle size	4 - 6mm Internal Methode
	Bulk density	450 - 650kg/m^3 STN EN ISO 60

Terms of Delivery:

REGRANULATE ABS-OST1-GRAY is delivered in a big bags placed on pallets, withs the weighing 1000 kg or more according to customer requirements. The packaging unit contains all the necessary product information as an indication of the manufacturer, product name, weight, date of manufacture. On the customer's request and by mutual agreement, the manufacturer may modify the method of packaging and to add some of the data in the labeling.
The product must be transported in dry and clean vehicles, stored in a covered, dry rooms and recommends a minimum of 48hours stored in a standard room conditions where it will be subsequently processed.

TATRAFAN, s.r.o.
Štúrova 101
059 21 Svit
Slovakia
tel.: +421 52 715 2685
fax: +421 52 715 7685
mail: milan.semancik@tatrafan.com