



REGRANULATE ON2

This data sheet serves as the general characteristics of the product to customer needs. It contains individual specifications, composition and use of this material.

REGRANULATE ON2 is made from waste of clear polypropylene film. Regranulate has the lentils shape, with the dimension 3-7 mm, and clear-natural colour. The regranulate is suitable for further processing into technical plastic products and consumer plastic items by injection molding, pressing or extrusion technology. Each customer is required to check, this material for the intended use.



TECHNICAL DATA

REGRANULATE ON2	Composition	100 % polypropylene, clear - natural
	Melt index	4,0 - 6,0g/10min./230°C/ STN EN ISO 1133
	Density	0,90 - 0,91g/cm³ ISO 1183
	Particle size	3 - 7mm Internal Methode
	Bulk density	400 - 600kg/m³ STN EN ISO 60

Terms of Delivery:

REGRANULATE ON2 is delivered in a big bags placed on pallets, with the weighing 1000 kg or more according to customer requirements. The packaging unit contains all the necessary product information as an indication of the manufacturer, product name, weight, date of manufacture. On the customer's request and by mutual agreement, the manufacturer may modify the method of packaging and to add some of the data in the labeling.

The product must be transported in dry and clean vehicles, stored in a covered, dry rooms and recommends a minimum of 48hours stored in a standard room conditions where it will be subsequently processed.



TATRAFAN, s.r.o.

Štúrova 101 059 21 Svit Slovakia

tel.: +421 52 715 2685 fax: +421 52 715 7685

mail: milan.semancik@tatrafan.com

enviro.tatrafan.com Edition: May 2017